

CLUSTERASIA CORP.

Powerful Round Disc Trencher for hard land, rocky ,concrete, cement etc.




Advantages

- Thicken the drive shaft;
- Steyr rear axle gearbox;
- The thickness of the plate is 16 mm, and the thickened ring is 25 mm;
- Strengthen double support wheels;
- Disc body stiffener,



Technical parameter		
Reference picture 	Alloy terminal teeth	122pcs
	Overall Dimensions Length*Width*Height	1.5*2*1.5m
	Operating speed	100--300(m/h)
	Furrow width	4inches=10cm
	Ditching depth	2fts=60 cm
	Disc diameter	1.6m
	Auxiliary power	50 HP
	Premium K23 Alloy terminal teeth	5 pcs free(extra if you need more)
	Teeth bases	5 pcs free(extra if you need more)



2)50 HP Tractor Technical Parameter

Drive mode	four-wheel drive	Power	50HP
PTO shaft speed	2400r/min	Overall size	3813*1640*2240mm
Max counterweight	144kg front /260kg after	Max traction	13kn
forward speed	2.69-32.46km/h	Back speed	3.98-11.71km/h
wheelbase	2030mm	front wheel track	1250mm
Min ground clearance	325mm	After wheel track	1300-1600mm
Rated power	37kw	Rated speed	2400r/min

